

## General Specifications

- Can be combined with carbon monoxide (CO) monitoring and other safeguards to help
- Constructed of heavy gauge steel
- Portable (excluding wall mount option)
- Filter supported by three legs (excluding wall mount option)
- Includes filter cartridge
- Optional Handle kit available
- Available with choice of 9 different, 1/4" quick disconnect coupler
  - Industrial Interchange (Hansen Compatible) in steel, brass or stainless steel
  - Snap-Tite in steel, brass or stainless steel
  - Schrader
  - CEJN
  - Bayonet
- European adapter kit available

## Technical Specifications

Airline Filter	Model 41A	Model 41P2	Model 41P6	Model 41P6WM	Model 41P2E
<b>Max. Air Flow Rate</b>	100 cfm* (2830 lpm)	75 cfm (2120 lpm)	75 cfm (2120 lpm)	75 cfm (2120 lpm)	75 cfm (2120 lpm)
<b>Inlet Connection</b>	1" NPT (Fem.)	1" NPT (Fem.)	1" NPT (Fem.)	1" NPT (Fem.)	3/4" (19 mm) NPT (Fem.)
<b>Outlet Connection</b>	1" NPT (Fem.)	2 outlets 3/8" NPT (Fem.)	6 outlets 3/8" NPT (Fem.)	6 outlets 3/8" NPT (Fem.)	2 outlets 1/4" (6 mm) BPT (Fem.)
<b>Relief Valve</b>	-	125 psig (8.6 bar)	125 psig (8.6 bar)	125 psig (8.6 bar)	125 psig (8.6 bar)
<b>Tank Diameter</b>	5 1/2" (14 cm)	5 1/2" (14 cm)	5 1/2" (14 cm)	5 1/2" (14 cm)	5 1/2" (14 cm)
<b>Height</b>	19" (48 cm)	23 1/2" (60 cm)	25 1/4" (64 cm)	22" (56 cm)	23 1/2" (60 cm)
<b>Weight</b>	19 lb. (8.6 kg)	22 lb. (10 kg)	24 lb (10.9 kg)	28 lb (12.7 kg)	22 lb (10 kg)
<b>*At maximum recommended pressure of 100 psig (6.9 bar)</b>					

## Filtration

- Designed to help trap and remove most of the following:
  - Oil and oil mist;
  - Particulate matter larger than 1/2 micrometer;
  - Odors and organic vapors; and
  - Excessive moisture
- 7-Stage Filtration System:
  - Water is removed by condensation against the cylinder wall
  - Carded cotton removes particulates
  - Active Alumina absorbs oil and moisture
  - Activated charcoal removes odors and moisture
  - Felt material removes particulates
  - Carded cotton removes particulates
  - Respiratory felt acts as a final filter before air is transferred to work or air driven tools.
- Large disposable filter cartridges to allow longer periods of filtration
- Weighs 6 lbs.

## Warranty

- 1 year limited manufacturer warranty for original purchaser from date of purchase

**Americas:**  
**E.D. Bullard Company**  
 1898 Safety Way  
 Cynthiana, KY 41031-9303  
 Toll free: 877-BULLARD (285-5273)  
 Tel: 859-234-6616  
 Fax: 859-234-8987  
[www.bullard.com](http://www.bullard.com)

**Europe:**  
**Bullard GmbH**  
 Lilienthalstrasse 12  
 53424 Remagen • Germany  
 Tel: +49-2642 999980  
 Fax : +49-2642 9999829  
[www.bullardextrem.com](http://www.bullardextrem.com)

**Asia-Pacific:**  
**Bullard Asia Pacific Pte. Ltd.**  
 LHK Building  
 701, Sims Drive, #04-03  
 Singapore 387383  
 Tel: +65-6745-0556  
 Fax: +65-6745-5176  
[www.bullard.com](http://www.bullard.com)

