

**Specifications**

- Two to Three person pump
- Oil-less – eliminates OSHA required CO monitors, temperature alarms, airline filters
- 1 1/2 horse power electric driven pump
- Made in the USA
- Portable (includes handles) and optional wheels
- Capacity to supply air to:
  - two hood-style; or
  - three half or full face mask airline respirators
- Pressure gauge (0-30 psig)
- Two 1/2" Industrial Interchange (Hansen compatible) quick-disconnect coupler
- Weights 98 lbs (44.5 kg)
- Air flow of 16 cfm at 5 psig. (453 lpm @ 34kPa)
- Dimensions: 14" wide x 28" long x 6" high
- Carbon vans are replaceable and need no adjustment, lasting for 5,000 – 15,000 operational hours if properly maintained.
- Maximum Outlet Air pressure of 30 psig
- 7 foot grounded electrical cord with a standard three-prong plug
- No calibration is required

**Electrical Motor Specifications**

- Totally enclosed fan-cooled motor drive (TFEC)
- Capacitor Start
- Enclosure meets UL requirements
- Enclosure is CSA Approved
- Natl. Elec. Code: Class III Division 1 and 2
- 1 1/2 horse power
- Single Phase
- 60 Hz cycle
- 115/208/230 Volts (115V standard)
- 16 amps @ 115 V
- 8.0 amps @ 208/230 V
- 1.15 Service Factor
- Manual Reset thermal overload equipped for 115V operation

**Filters**

- Breathable air inlet can be located up to 300 feet away from the pump
- Medium efficiency Inlet Filter (particulates large than 25 microns filtered out of the air supply). Replace after 500 operational hours or less depending on working conditions.
- Outlet filter is Carbofine with activated carbon. Replace after 200 operational hours or less depending on working conditions.

**Respirator Capabilities**

- May be used in conjunction with any manufacture's supplied air respirators. Check the respirator's owner's manual to verify that the cfm output of the pump is adequate.
- Minimum Air Flow required for each tight-fitting mask style respirator is four (4) cfm
- Minimum Air Flow required for each hood style respirator is six (6) cfm.

**Warranty**

1 year limited warranty to original purchaser from date of purchase.

**Americas:**

**E.D. Bullard Company**  
1898 Safety Way  
Cynthiana, KY 41031-9303  
Toll free: 877-BULLARD (285-5273)  
Tel: 859-234-6616  
Fax: 859-234-8987  
[www.bullard.com](http://www.bullard.com)

**Europe:**

**Bullard GmbH**  
Lilienthalstrasse 12  
53424 Remagen • Germany  
Tel: +49-2642 999980  
Fax : +49-2642 9999829  
[www.bullardextrem.com](http://www.bullardextrem.com)

**Asia-Pacific:**

**Bullard Asia Pacific Pte. Ltd.**  
LHK Building  
701, Sims Drive, #04-03  
Singapore 387383  
Tel: +65-6745-0556  
Fax: +65-6745-5176  
[www.bullard.com](http://www.bullard.com)

