

<b>Respirator Type</b>	Continuous flow airline respirator for use with ambient air pumps or compressed air
<b>Components</b>	<ul style="list-style-type: none"><li>• Respirator Hood</li><li>• Suspension Headband or Bullard Hard Hat</li><li>• Breathing Tube Assembly</li><li>• Breathing Air Supply Hose</li></ul>
<b>Approvals</b>	<ul style="list-style-type: none"><li>• Meets ANSI Z89.1-2009 Head Protection Requirements when used with Bullard Hard Hat</li><li>• Meets ANSI Z87.1-2009 Face Protection Requirements (High Impact Penetration)</li><li>• NIOSH Approved Type C respirator</li></ul>
<b>Hood</b>	<ul style="list-style-type: none"><li>• No fit test required</li><li>• Independent, 3rd party, 1000 APF Available</li><li>• Accommodates beards, hearing protection, prescription eyewear or safety glasses</li><li>• Weighs 12 oz. (340g)</li><li>• Outer hood made of Nomex<sup>®</sup></li><li>• 12" long outer bib</li><li>• Inner bib made from Westex flame-retardant cotton</li><li>• Hood may be laundered up to 50 times industrially and 25 times at home</li><li>• Can be used for grinding, metalworking, or painting</li><li>• Unique neck cuff helps maintain positive pressure and helps keep contaminants out</li><li>• Inner Window made of .040" Polycarbonate</li><li>• Replaceable outer lens available in .04" Polycarbonate or .02 Acetate</li><li>• Wide-angle face shield with a visible area of approx 13.25" X 6"</li><li>• Approved for use with up to 300 feet of airline supply hose</li><li>• Optional adhesive-backed Mylar<sup>®</sup> Lens covers</li></ul>
<b>Optional Bullard Hard Hat</b>	<ul style="list-style-type: none"><li>• Offers two cap style hard hats (C30 or S51)</li><li>• Hard hats made out of high-density polyethylene shell</li><li>• Accessory slots for attachments</li><li>• C30 offers 6-point Flex-Gear ratchet or pinlock suspension with large absorbent cotton brow pad with vertical height adjustment (two front, three rear)</li><li>• S51 offers 4-point Flex-Gear ratchet or pinlock suspension with large poly brow pad with vertical height adjustment (two front, two rear)</li><li>• Replacement suspensions for all hard hats available</li><li>• Replaceable brow pad available in (Poly, Cotton and Vinyl)</li></ul>
<b>Suspension Headband Only</b>	<ul style="list-style-type: none"><li>• Adjustable Flex gear Ratchet or pinlock headband suspension</li><li>• Large poly brow pad</li><li>• Four point comfort cradle in place of crown straps</li><li>• Replaceable brow pad available in (Poly, Cotton and Vinyl)</li><li>• Fits head sizes 6 1/2 to 8 (52-64mm)</li><li>• Vertical Height adjustment (two front, two rear)</li></ul>

## Breathing Tube Assembly

- Offers 3 different breathing tube covers made of Tychem® QC, Tychem® SL or clear Poly.
- Approved and available with constant or adjustable flow control device with 1/2" Industrial Interchange (Hansen compatible) quick disconnect coupler for ambient air pumps.
- Approved and available with constant or adjustable flow control device with 9, 1/4" quick disconnect coupler for compressed air pumps.
  - Industrial Interchange (Hansen Compatible) in steel, brass or stainless steel
  - Snap-Tite in steel, brass or stainless steel
  - Schrader
  - CEJN
  - Bayonet
- Standard Nylon belt or optional Decontamination belt

## Airline Supply Hose

- NIOSH approved for use with 25-300 feet of airline supply hose for compressed air.
- NIOSH approved for use with 50-300 feet of airline supply hose for ambient air pumps
- Choice of neoprene reinforced rubber 3/8" I.D. hose or nylon coiled hose for compressed air. 1/2" ID hose for ambient air pumps.
- Manufactured specifically to carry breathing air
- Offers 1/2" industrial interchange (Hansen compatible) nipple for ambient air pumps
- Offers 9, 1/4" approved quick disconnect couplers compatible with breathing tube fittings for compressed air
  - Industrial Interchange (Hansen Compatible) in steel, brass or stainless steel
  - Snap-Tite in steel, brass or stainless steel
  - Schrader
  - CEJN
  - Bayonet

## Compressed Air Optional

- NIOSH approved for use with Bullard's GR50
- Cool and Hot/Cold tubs available (AC1000)
  - Cools incoming air by as much as 30 F (17 C)
  - Adjustable airflow control valve for individual comfort
- Hot/Cold Tube (HC2400)
  - Cools or warms incoming air by as much as 30 F (17 C)
  - Adjustable airflow control valve for individual comfort
  - Change between cooled or warmed air in seconds
- Dual-Cool (DC5040)
  - Cools incoming air by as much as 30 F (17 C).
  - Cools air supplied to both hood and cooling vest
  - Separate control knobs allow adjustment of the temperature of air to each zone
  - Compressor must have the capacity to supply a minimum of 30 cfm (850lpm) of air
- Cooling Vest (DC70)
  - Sizes M, L, XL, XXL
  - Can be used without respirator

## Warranty

1 year limited manufacturer warranty for original purchaser from date of purchase

**Americas:**  
**E.D. Bullard Company**  
1898 Safety Way  
Cynthiana, KY 41031-9303  
Toll free: 877-BULLARD (285-5273)  
Tel: 859-234-6616  
Fax: 859-234-8987  
[www.bullard.com](http://www.bullard.com)

**Europe:**  
**Bullard GmbH**  
Lilienthalstrasse 12  
53424 Remagen • Germany  
Tel: +49-2642 999980  
Fax : +49-2642 9999829  
[www.bullardextrem.com](http://www.bullardextrem.com)

**Asia-Pacific:**  
**Bullard Asia Pacific Pte. Ltd.**  
LHK Building  
701, Sims Drive, #04-03  
Singapore 387383  
Tel: +65-6745-0556  
Fax: +65-6745-5176  
[www.bullard.com](http://www.bullard.com)



©2011 Bullard. All rights reserved.